
FIGURE 1. MESA FINAL WATER BALANCE WITH HERO



**Table 1. Estimated Water Savings Before 2001** 

		Water Savings		% Reduction	
		Min.	Max.		
Description		(MGals.)	(MGals.)	Min	Max
	More precise control valves, more				
	efficient pump manifold, high-surface-				
MDL - Reverse	area RO membranes, upgraded				
Osmosis (1996)	piping.	30	38	6.7%	7.9%
	Separate, monitor and recycle rinse				
MDL - Process	water. Recycle acid from process	_			
Changes (1998)	tank discharge.	2	2	0.4%	0.4%
MDL - Cooling	Use process waste water for cooling				
Towers ( 1998)	tower feed.	25	30	5.6%	6.2%
	Steam and condensate line leak				
	detection and repair. Replace				
	dealkalyzer. Add caustic to brine for				
Steam Plant	resin renewal. Recycle treated water				
Improvements	for cooling fan bearings, feedwater				
(1996)	pumps, and conductivity meter	15	25	3.3%	5.2%
Laser Cooling Loop					
at CSRL	Replace once-through cooling system				
(Completed in	for CSRL lasers with closed-loop				
1998)	system.	5	15	1.1%	3.1%
	Total Water Saved Million Gallons				
TOTAL	Per Year	77	110	17.2%	22.9%

